

Mercury Marine
W6250 Pioneer Rd.
PO Box 1939
Fond du Lac, WI 54935

MATERIAL SAFETY DATA SHEET

MARINE LUBRICANT WITH TEFLON

1. PRODUCT AND COMPANY IDENTIFICATION

TRADE NAME Mercury Precision 2-4-C Marine Lubricant with Teflon

PART No. 92-802859A 1, 92-802861A 1, 92-802863A 1
(This product included in these kits:91-30500A 5, 91-30500K 2, 91-74057A 4, 91-74057A 6, 91-74057K 5)

PRODUCT USE Lubricating Grease

INFORMATION TELEPHONE (920) 929-5000

EMERGENCY TELEPHONE ChemTrec (U.S. Only) (800) 535-5053

Date of last issue 08/10/2006

2. COMPOSITION AND INFORMATION ON INGREDIENTS

INGREDIENT NAME	CAS No.	WEIGHT
LUBRICATING OILS, PETROLEUM, BASE OILS, HIGHLY REFINED**(2)	Mixture	70-85 %
*OCTADECANOIC ACID, 12-HYDROXY-, MONOLITHIUM SALT	7620-77-1	7-13 %
ETHENE, TETRAFLUORO-, HOMOPOLYMER (COMMON NAME: POLYTETRAFLUOROETHYLENE)	9002-84-0	1-5 %
*PHOSPHORODITHIOIC ACID, O,O-DI-C1-14-ALKYL ESTERS, ZINC SALTS (TYPE B)	68649-42-3B	1-4 %

* This chemical(s) is hazardous according to OSHA/WHIMIS criteria

COMPOSITION COMMENTS Refer to section eight for exposure limits on ingredients.
Chemical ingredients not regulated by OSHA or SARA are treated confidentially.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Not regarded as a health hazard under current legislation. Exposure to vapors generated at high temperatures may cause respiratory irritation.

SENSITIZATION	No known information.
CARCINOGENICITY	IARC: Not listed as a Group 1, 2A, or 2B agent. OSHA: Not regulated. NTP: Not listed.
TERATOGENICITY	No known information.
HEALTH WARNINGS	SKIN CONTACT. Repeated or prolonged contact can result in drying of the skin. EYE CONTACT. Irritating. INGESTION. Can cause stomach ache and vomiting. INHALATION. Heating can generate vapors that may cause respiratory irritation, nausea and headaches. Inhalation hazard at room temperature is unlikely due to the low volatility of this product.
ROUTE OF ENTRY	Inhalation. Skin and/or eye contact. Ingestion.

4. FIRST AID MEASURES

INHALATION	Move the exposed person to fresh air at once. For breathing difficulties oxygen may be necessary. Get medical attention if any discomfort continues.
EYES	Rinse with water. Contact physician if discomfort continues.
SKIN	Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
INGESTION	DO NOT INDUCE VOMITING! Get medical attention immediately!

5. FIRE FIGHTING MEASURES

FLASH POINT (°C)	224 (435°F) Cd OC (Cleveland open cup).
FLAMMABILITY LIMIT - LOWER(%)	N/D
FLAMMABILITY LIMIT - UPPER(%)	N/D
EXTINGUISHING MEDIA	Use: Foam. Carbon dioxide (CO2). Dry chemicals, sand, dolomite etc.
SPECIAL FIRE FIGHTING PROCEDURES	Use water to keep fire exposed containers cool and disperse vapors. Water spray may be used to flush spills away from exposures and dilute spills to non-flammable mixtures. Keep run-off water out of sewers and water sources. Dike for water control.
UNUSUAL FIRE & EXPLOSION HAZARDS	Volume and pressure increases strongly when heated. Risk of container explosion in fire. Explosion risk when heated. Aerosol cans may explode in case of fire.
HAZARDOUS COMBUSTION PRODUCTS	Acrid smoke/fumes. Hydrogen fluoride (HF). Oxides of: Carbon. Phosphorus. Sulfur.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS	Minimize skin contact. Avoid breathing vapors. Wear an appropriate respirator if exposure exceeds recommended guidelines. Remove sources of ignition.
PRECAUTIONS TO PROTECT THE ENVIRONMENT	Keep product out of sewers and watercourses by diking or impounding. Advise authorities if product has entered or may enter sewers, watercourses or extensive land areas. Assure conformity with applicable government regulations.
SPILL CLEAN-UP PROCEDURES	Carefully collect spilled material in closed containers and leave for disposal

according to local regulations. Provide good ventilation. Use appropriate protective clothing. Rinse area with water. Do not let washing down water contaminate ponds or waterways.

7. HANDLING AND STORAGE

HANDLING PRECAUTIONS

Avoid spilling, skin and eye contact. Keep away from heat, sparks and open flame. Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Containers to be kept tightly closed. Eye wash and emergency shower must be available at the work place.

STORAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Store separated from: Oxidizing materials. Acids.

STORAGE CRITERIA

Chemical storage.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

COMPONENT	STD	TWA	STEL	TWA	STEL
LUBRICATING OILS, PETROLEUM, BASE OILS, HIGHLY REFINED**(2)	OSHA			5 mg/m3 (oil mist)	
	ACGIH			5 mg/m3 (oil mist)	10 mg/m3 (oil mist)

PROTECTIVE EQUIPMENT



ENGINEERING CONTROLS

Use engineering controls to reduce air contamination to permissible exposure level.

VENTILATION

No specific ventilation requirements noted, but forced ventilation may still be required if air contamination exceeds acceptable level.

RESPIRATORS

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

PROTECTIVE GLOVES

Chemical resistant gloves required for prolonged or repeated contact.

EYE PROTECTION

Wear splash-proof eye goggles to prevent any possibility of eye contact.

PROTECTIVE CLOTHING

Wear appropriate clothing to prevent repeated or prolonged skin contact.

HYGIENIC WORK PRACTICES

Wash at the end of each work shift and before eating, smoking and using the toilet.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE/PHYSICAL STATE

Grease.

COLOR

Amber.

ODOR	Mild (or faint). Petroleum.		
SOLUBILITY DESCRIPTION	Insoluble in water.		
DENSITY	0.90	Temperature (°C)	15.6 (60°F)
VAPOR DENSITY (air=1)	> 5		
VAPOR PRESSURE	< 0.1 mmHg	Temperature (°C)	20 (68°F)
EVAPORATION RATE	< 1	Reference	BuAc=1
pH-VALUE, CONC. SOLUTION	N/A		

10. STABILITY AND REACTIVITY

STABILITY	Normally stable.
CONDITIONS TO AVOID	Avoid contact with acids and oxidizing substances.
HAZARDOUS POLYMERIZATION	Will not polymerize.
HAZARDOUS DECOMPOSITION PRODUCTS	Hydrogen fluoride (HF). Oxides of: Carbon. Phosphorus. Sulfur.

11. TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION No experimental toxicological data on the preparation as such is available.

COMPONENT LUBRICATING OILS, PETROLEUM, BASE OILS, HIGHLY REFINED**(2)

TOXICOLOGICAL DATA Carcinogenicity . IP 346 <3%
TOXIC DOSE - LD 50 > 5000 mg/kg (oral rat)
TOXIC DOSE - LD 50 SKIN > 2000 mg/kg (skn rbt)
TOXIC CONC. - LC 50 N/A.

COMPONENT OCTADECANOIC ACID, 12-HYDROXY-, MONOLITHIUM SALT

TOXIC DOSE - LD 50 N/A.
TOXIC CONC. - LC 50 N/A.

12. ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION No data on possible environmental effects have been found.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS Dispose of in accordance with Local Authority requirements.

14. TRANSPORT INFORMATION

DOT HAZARD CLASS Not regulated.

TDGR CLASS Not Regulated.

SEA TRANSPORT NOTES Not regulated per IMDG.

AIR TRANSPORT NOTES Not regulated per IATA.

15. REGULATORY INFORMATION

US FEDERAL REGULATIONS

COMPONENT	SARA 302	CERCLA	SARA 313
LUBRICATING OILS, PETROLEUM, BASE OILS, HIGHLY REFINED**(2)	No	No	No
OCTADECANOIC ACID, 12-HYDROXY-, MONOLITHIUM SALT	No	No	No
ETHENE, TETRAFLUORO-, HOMOPOLYMER (COMMON NAME: POLYTETRAFLUOROETHYLENE)	No	No	No
PHOSPHORODITHIOIC ACID, O,O-DI-C1-14-ALKYL ESTERS, ZINC SALTS (TYPE B)	No	***	N982 - Zn

REGULATORY STATUS

*** Indicates that no RQ is assigned to this generic or broad class, although the class is a CERCLA hazardous substance. See 50 Federal Register 13456 (April 4, 1985). Values in Section 313 column represent Category Codes for reporting under Section 313.

CLEAN AIR ACT

SARA HAZARD CATEGORIES None

US STATE REGULATIONS

COMPONENT	CA	MA	FL	MN	NJ	PA	RI
LUBRICATING OILS, PETROLEUM, BASE OILS, HIGHLY REFINED**(2)					Yes	Yes	
PHOSPHORODITHIOIC ACID, O,O-DI-C1-14-ALKYL ESTERS, ZINC SALTS (TYPE B)				Yes	Yes	EH	

STATE REGULATORY STATUS

CALIFORNIA PROPOSITION 65: This product may contain the following chemical(s) considered by the State of California's Safe Drinking Water and Toxic Enforcement Act of 1986 as causing cancer or reproductive toxicity, and for which warnings are now required:

1-Naphthylamine, CAS # 134-32-7, <1ppm

2-Naphthylamine, CAS # 91-59-8, <1ppm.

Cadmium <1ppm

Arsenic <1ppm

Lead <1ppm

PENNSYLVANIA RIGHT-TO-KNOW: This product contains the following chemicals that the state of Pennsylvania has identified as Special Hazardous Substances (SHS),

Environmental Hazards (EH), or both (ESHS). The PA regulations require that the MSDS identify all SHS or EH chemicals by chemical name, common name, and CAS Number if they comprise 0.01% or more.

Zinc compounds regulated under CERCLA and SARA 313, Environmental Hazard

WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM - WHMIS

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

CONTROLLED PRODUCT CLASSIFICATION

Not a controlled product.

COMPONENT	GLOBAL INVENTORIES								
	CAN	US	EU	AUS	JAP	KOR	PHLP	CHN	
LUBRICATING OILS, PETROLEUM, BASE OILS, HIGHLY REFINED**(2)	DSL	Yes	EINECS	Yes	Yes	Yes	Yes	Yes	
OCTADECANOIC ACID, 12-HYDROXY-, MONOLITHIUM SALT	DSL	Yes	EINECS	Yes	Yes	Yes	Yes	Yes	
ETHENE, TETRAFLUORO-, HOMOPOLYMER (COMMON NAME: POLYTETRAFLUOROETHYLENE)	DSL	Yes	Polymer	Yes	Yes	Yes	Yes	Yes	
PHOSPHORODITHIOIC ACID, O,O-DI-C1-14-ALKYL ESTERS, ZINC SALTS (TYPE B)	NPRI	Yes	EINECS	Yes	Yes	Yes	Yes	Yes	

CANADA CEPA: All components of this product comply with new substance notification requirements under the Canadian Environmental Protection Act (CEPA).

16. OTHER INFORMATION

NFPA-HMIS HAZARD RATING

HEALTH	Irritation, minor residual injury (1) - HMIS/NFPA
FLAMMABILITY	Burns only if pre-heated (1) - HMIS/NFPA
REACTIVITY	Normally Stable (0) - HMIS/NFPA
PERSONAL PROTECTION INDEX	B - Safety Eyewear and Gloves
REVISION COMMENTS	Section 2: Ingredients Section 15: Inventory Status Section 15: US Regulatory Status.
PREPARED BY	Heather Holich
Replacement MSDS of	2002-12-16
DATE	2006-08-10
PRINTING DATE:	2006-08-10
DISCLAIMER	While the information and recommendations set forth herein are believed to be accurate as of the date thereof, the company makes no warranty with respect thereto and disclaims all liability from reliance therein.

MFR: Chemtool Incorporated, P.O. Box 538, 8200 Ridgefield Road, Crystal Lake, IL 60039-0538 USA

* Information revised since previous MSDS version

