

MSDS 223-6134KC

Issued to : Mercury Marine (09036)
P. O. Box 1337

Fond du Lac, WI 54936-1337

Attention: : Material Safety Data Sheet Coordinator

The attached Material Safety Data Sheet relates potential hazards and recommended practices for safe handling of the product that you purchased from Raabe Company.

We urge you and your employees to review the entire MSDS prior to handling, use or disposal of the product.

You are required to keep this MSDS on file for reference by company employees or government regulatory officials.

If you resell or distribute this product, you must furnish a copy of the MSDS to your customer.

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

CHEMICAL PRODUCT IDENTIFICATION:

Part Number : 92-858080KC2
PRODUCT NAME : POWER TUNE ENGINE CLEANER/NETTOYANT DE MOTEUR
PRODUCT CLASS : Aerosol Touch-Up

MSDS PREPARATION DATE : 08/18/2009

MANUFACTURER IDENTIFICATION:

RAABE COMPANY
PO BOX 1090
MENOMONEE FALLS, WI 53052-1090

CUSTOMER IDENTIFICATION:

Mercury Marine
P. O. Box 1337
Fond du Lac, WI 54936-1337

General Information: (920) 929-5000

EMERGENCY TELEPHONE NUMBERS:

24 HOURS A DAY - CALL CHEMTREC : 800-424-9300
INTERNATIONAL CALLS TO CHEMTREC : 703-527-3887
8 AM TO 4:30 PM CENTRAL TIME : 262-255-9500

SECTION 2 - COMPOSITION, INFORMATION ON INGREDIENTS

1 HEAVY NAPHTHENIC DISTILLATE

CAS# 64742-52-5
HEAVY NAPHTHENIC DISTILLATE
PCT BY WT: 72.0000
EXPOSURE LIMIT:

ACGIH TLV-TWA 5 mg/m3 (Mist)
OSHA PEL-TWA 5 mg/m3 (Mist)

2 MINERAL SPIRITS

CAS# 64741-65-7
 MINERAL SPIRITS
 PCT BY WT: 10.0000 LEL 1.00
 EXPOSURE LIMIT:
 ACGIH TLV-TWA 200 ppm
 ACGIH TLV-STEL NO INFO

3 N-BUTANE
 CAS# 106-97-8
 N-BUTANE
 PCT BY WT: 3.0000 VAPOR PRESSURE: 879.100 MMHG @ 68F LEL 1.80
 EXPOSURE LIMIT:
 ACGIH TLV-TWA 800 ppm
 ACGIH TLV-STEL NO INFO
 OSHA PEL-TWA 800 ppm
 COMPANY N. E.
 LD50(ORAL) N. A.
 LD50(DERMAL) N. A.
 LC50 658000 mg/m3 (rat)
 OTHER LIMITS: EINECS 203-448-7

4 PROPANE
 CAS# 74-98-6
 PROPANE
 PCT BY WT: 7.0000 VAPOR PRESSURE: 5585.200 MMHG @ 68F LEL 2.20
 EXPOSURE LIMIT:
 ACGIH TLV-TWA 1000 ppm
 ACGIH TLV-STEL NO INFORMATION
 LD50(ORAL) NOT APPLICABLE
 LD50(DERMAL) NOT APPLICABLE
 LC50 NO INFORMATION
 OTHER LIMITS: EINECS 200-827-9

5 SURFACTANT
 CAS# 9016-45-9
 NONIONIC SURFACTANT
 PCT BY WT: 8.0000
 EXPOSURE LIMIT:
 ACGIH TLV-TWA *NOT
 ACGIH TLV-STEL ESTABLISHED*

 This product contains no reported carcinogens or suspected
 carcinogens.

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:
 May cause skin irritation.
 Extremely flammable liquid and vapor.
 Vapors may cause flash fire or explosion.
 Extremely flammable aerosol.
 Contents under pressure.
 EYE:
 May cause eye irritation.
 SKIN:
 INHALATION:
 Exposure to high concentrations of vapors may cause dizziness, breathing
 difficulty, headaches or respiratory irritation.

Extremely high concentrations may cause drowsiness, staggering, confusion, unconsciousness, coma or death.

INGESTION:

Moderately toxic. May cause stomach discomfort, nausea, vomiting, diarrhea, and narcosis.

CHRONIC EFFECTS:

The surfactant in this product may emit traces of ethylene oxide (CAS#: 75-21-8) refer to 29 CFR 1910.1047 for current OSHA regulations.

SECTION 4 - FIRST AID MEASURES

EYE CONTACT:

Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

SKIN CONTACT:

Wash thoroughly with soap and water and seek medical attention if irritation persists. Remove contaminated clothing. Launder contaminated clothing before reuse.

INHALATION:

For inhalation overexposure move person to fresh air. If breathing stops, apply artificial respiration and seek medical attention.

INGESTION:

Do not induce vomiting which can cause chemical pneumonitis and pulmonary edema. Contact a physician immediately.

SECTION 5 - FIRE FIGHTING MEASURES

FIRE AND EXPLOSIVE PROPERTIES OF THE PRODUCT:

Flashpoint : Less Than -25 øF
Explosion Level : Low (LEL) - 1.0
High (UEL)- 9.5

EXTINGUISHING MEDIA:

Use Dry Chemical, Carbon Dioxide or Chemical Foam.

FIRE-FIGHTING PROCEDURES AND EQUIPMENT:

Contents under pressure. Do not use or store near sources of heat, sparks or open flame. Keep away from any source of heat such as sunlight, heaters or stoves that could cause the container to burst. Do not puncture or incinerate. Do not crush or place in a garbage compactor. Do not store above 120 degrees F. Aerosol containers may explode when exposed to extreme heat. Product vapors are heavier than air and may travel a long distance to a source of ignition and flash back. Full protective equipment including self-contained breathing apparatus to avoid inhalation of vapors should be used. Water spray should not be used except to keep down vapors or cool closed containers to prevent build-up of pressure. If water is used, fog nozzles are preferred.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

CLEAN-UP AND CONTAINMENT:

Remove all sources of ignition. Avoid heat, sparks, flames and anything which could cause fire. Ventilate area of spill and adjacent low lying areas. Avoid breathing solvent vapors. Remove with inert absorbent materials and non-sparking tools.

SECTION 7 - HANDLING AND STORAGE

HANDLING:

Wash hands thoroughly after handling.

STORAGE:

Store in a cool dry area with ventilation suitable for storing materials shown in section 2.

Store this product indoors to protect from freezing.

Keep away from heat, sparks and flame.

Store in a cool place away from direct sunlight or any source of ignition. Do not store at temperatures above 120 degrees F.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

ENGINEERING CONTROLS:

Sufficient ventilation, in volume and pattern, should be provided to keep air contamination below current applicable OSHA permissible exposure limit or ACGIH's TLV limit.

RESPIRATORY PROTECTION:

If workplace exposure limits are exceeded for any component(see section 2 for hazardous components and exposure limits), a NIOSH/OSHA approved respirator suitable for components listed is recommended.

SKIN PROTECTION:

Chemical resistant plastic or rubber gloves recommended for prolonged or repeated contact.

EYE PROTECTION:

Chemical goggles with side shields or face shield recommended if contact with the eyes is likely.

OTHER PROTECTIVE EQUIPMENT:

Appropriate impervious clothing is recommended if prolonged or repeated contact is likely.

HYGIENIC PRACTICES:

Wash hands before eating or smoking. Smoke in designated areas only.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Vapor Pressure	:	5585.20	mm Hg @ 20 C
Vapor Density	:	-N/A	
Boiling Range	:	Lower - 1.0	øF
		Higher - 520.0	øF
Specific Gravity	:	.839	
Formula Weight per Volume	:	6.9844	LB/GL
VOC (Calculated, LB/GAL)	:	6.427	
VOC (Calculated, GM/L)	:	770.14	
Percent Volatile by Weight.	:	91.9820	
Percent Volatile by Volume	:	93.6412	
Evaporation Rate	:	.100	(n-Butyl Acetate = 1)
Viscosity	:	-N/A	

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID:

Avoid contact with heat, sparks, and open flame.
Product may explode if heated. Keep cool, avoid exposure to heat.

INCOMPATIBILITIES:

Strong oxidizing agents.

DECOMPOSITION:

Thermal decomposition may produce carbon dioxide, carbon monoxide, and unidentified organic materials.

POLYMERIZATION:

No hazardous polymerization will occur under normal conditions.

STABILITY:

The product is stable under normal storage conditions.

SECTION 11 - TOXICOLOGICAL INFORMATION

No specific information is available. Please refer to Section 2 and 3 for available information on exposure limits and hazards identification.

SECTION 12 - ECOLOGICAL INFORMATION

No specific ecological information is available for this product.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:

Place in closed containers. Dispose of product in accordance with local, county, state, and federal regulations.

SECTION 14 - TRANSPORT INFORMATION

Ground shipment of limited or excepted quantities of aerosols or liquid paint in containers of 1 quart or less:

CONSUMER COMMODITY, ORM-D

Ground shipment of liquid paint in containers more than 1 quart:

PAINT, FLAMMABLE LIQUID, UN1263, CLASS 3, GROUP II

(Regulatory sources: DOT 49CFR 172.101)

Air shipment of limited or excepted quantities of aerosols or liquid paint in containers of 1 quart or less:

CONSUMER COMMODITY, ID 8000, CLASS 9 MISCELLANEOUS LABEL

(Regulatory sources: IATA Quantity Exemptions - Table 2.8.4, 2.7.A, 2.7.5, Packaging Instruction: 910)

OR

AEROSOLS, FLAMMABLE, UN1950, CLASS 2.1 LABEL

(Regulatory sources: IATA Quantity Exemptions - Table 2.8.1, 2.8.4, Packaging Instruction: Y203)

SECTION 15 - REGULATORY INFORMATION

SARA 313 INFORMATION:

This product contains NONE of the substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

FEDERAL REGULATIONS:

TOXIC SUBSTANCES CONTROL ACT: The chemical substances in this product are listed on the TSCA Section 8 inventory.

STATE REGULATIONS:

This product contains chemical(s) which are listed on California's proposition 65 list. If the product is to be sold or used in California a clear and reasonable warning must be provided such as:

Warning! This product contains a chemical or chemicals known to the State of California to cause cancer.

NEW JERSEY RIGHT-TO-KNOW

No non-hazardous ingredients are among the top five ingredients

PENNSYLVANIA RIGHT-TO-KNOW

No non-hazardous ingredients are present greater than 3%

INTERNATIONAL REGULATIONS:

CANADA: The chemical substances in this product are listed on the Canadian Domestic Substances List.

SECTION 16 - OTHER INFORMATION

The information contained on this MSDS is believed to be reliable and accurate. Due to the changing nature of government information, it is impossible to guarantee the accuracy of the information contained herein. Since the conditions of handling and use are beyond our control, we make

RZ103123.TXT

no guarantee of results and assume no liability for damages incurred by the use of this material. This information should not be regarded as legal advice or regulation. It is the responsibility of the user to comply with all Federal, State, and Local laws and regulations. For questions relating to specific aspects of the requirements and regulations consult the proper regulatory agency.

HMIS RATINGS:

HEALTH: 2* FLAMMABILITY: 4 REACTIVITY: 0 PERSONAL PROTECTION: X

0