

**Product:** Marine Light Penetrating Oil - Aerosol**Product #:** 92-881093K 1**SECTION I - MANUFACTURER INFORMATION****Name:** Mercury Marine**Emergency:** 800-424-9300 (ChemTrec)**Address:** W6250 W. Pioneer Rd.**Information:** 920-929-5418

PO Box 1939

**Date Prepared:** 09-18-00

Fond du Lac WI 54936-1939

**Revised:****SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION**

Hazardous Components*	OSHA PEL	ACGIH TLV	Other	% (Opt.)
Distillates, Petroleum, Solvent-Dewaxed Heavy Paraffinic(64742-65-0)	5mg/m <sup>3</sup>	5mg/m <sup>3</sup>		10-30
Stoddard Solvent (8052-41-3)	100ppm	100ppm		50-70
Carbon Dioxide (124-38-9)	10,000ppm	5,000ppm		1-5

\*Specific Chemical Identity, Common Name (CAS)

**SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS****Boiling Point:** N/D**Specific Gravity (H<sub>2</sub>O=1):** 0.82**Vapor Pressure (mmhg):** N/D**Melting Point:** 0°F**Vapor Density (Air=1):** > 1**Evaporation Rate:** < 1**Solubility in Water:** Insoluble in water.**(Butyl Acetate=1)****Appearance and Odor:** Aerosol; mild solvent odor.**HMIS Rating:** H-1 F-N/D R-N/D P-Section VIII**SECTION IV - FIRE AND EXPLOSION HAZARD DATA****Flash Point (Method Used):** 120°F (TCC)**NFPA Rating:** H-1 F-4 R-0 S-N/A**Flammable Limits:** LEL - 0.7 UEL - 10**Extinguishing Media:** Foam, carbon dioxide (CO<sub>2</sub>), dry chemicals, sand, dolomite, etc.

**Special Fire Fighting Procedures:** Use water to keep fire-exposed containers cool and disperse vapors. Water spray may be used to flush spills away from exposures and dilute spills to non-flammable mixtures. Keep run-off water out of sewers and water sources. Dike for water control. Self-contained breathing equipment and chemical-resistant clothing recommended.

**Unusual Fire and Explosion Hazards:** Volume and pressure increases strongly when heated. Risk of container explosion in fire. Explosion risk when heated. Aerosol cans may explode in case of fire.

**SECTION V - REACTIVITY DATA****Stability:** Unstable ( ) Stable (X)

**Conditions to Avoid:** Contact with acids and oxidizing substances. Avoid heat, flames and other sources of ignition.

**Incompatibility (Materials to Avoid):** N/D**Hazardous Decomposition or Byproducts:** Oxides of carbon and hydrocarbons**Hazardous Polymerization:** May Occur ( ) Will Not Occur (X)**ADDITIONAL INFORMATION**

Mercury Marine Emergency Information Number: 920-929-5000

Manufacturer, Chemtool Inc., Emergency Number: 815-459-1250

**SECTION VI - HEALTH HAZARD DATA**

**Route(s) of Entry:** Inhalation (Y) Skin (Y) Eye (Y) Ingestion (Y)

**Health Hazards (Acute and Chronic):** Irritating to eyes, respiratory system, and skin.

**Carcinogenicity:** NTP (N) IARC Monographs (N) OSHA Regulated (N)

**Signs and Symptoms of Exposure:** Inhalation – The solvent vapors can be harmful and cause headache, nausea, and intoxication. Prolonged inhalation of large concentrations can damage the respiratory system. Skin – Slightly irritating. Repeated or prolonged contact can result in drying of the skin. Eye – Irritating. Ingestion – Since the quantity in an aerosol is limited and product is hard to ingest, the toxicity risk is deemed to be small. Can cause stomach ache and vomiting.

**Medical Conditions Generally Aggravated by Exposure:** N/D

**Emergency and First Aid Procedures:** Inhalation – Remove victim immediately from source of exposure. Move the exposed person to fresh air at once. For breathing difficulties, oxygen may be necessary. If breathing stops, provide artificial respiration. Get medical attention. Skin – Remove contaminated clothing. Wash affected skin thoroughly with soap and water. Get medical attention if any discomfort continues. Eye – Rinse the eye with water immediately. Continue to rinse for about 15 minutes. Get medical attention if any discomfort continues. Ingestion – DO NOT INDUCE VOMITING! Get medical attention immediately.

**SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE**

**Steps to be Taken in Case Material is Released or Spilled:** Provide good ventilation. Carefully collect spilled material in closed containers and leave for disposal according to local regulations. Rinse area with water. Do not let washing-down water contaminate ponds or waterways. Keep product out of sewers and watercourses by diking or impounding. Advise authorities if product has entered or may enter sewers, watercourses, and extensive land areas. Assure conformity with applicable government applications.

**Waste Disposal Method:** Dispose of in accordance with local authority requirements.

**Precautions to be taken in Handling and Storing:** Containers to be kept tightly closed. Store separate from strong acids and oxidizers. Keep away from heat, sparks and open flame. Protect aerosol cans from direct sunlight and do not subject to temperatures above 122°.

**Other Precautions:** KEEP AWAY FROM CHILDREN!

**SECTION VIII - CONTROL MEASURES**

**Respiratory Protection (Specify Type):** No specific recommendation made. Respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

**Ventilation: Local Exhaust & Mechanical:** No specific ventilation requirements are noted, but forced ventilation may still be required if air contamination exceeds acceptable level.

**Protective Gloves:** Chemical-resistant gloves required for prolonged or repeated contact.

**Eye Protection:** Wear splash-proof eye goggles to prevent any possibility of eye contact.

**Other Protective Clothing or Equipment:** Wear appropriate clothing to prevent repeated or prolonged skin contact.

**Work/Hygiene Practices:** Always follow good housekeeping and personal hygiene practices.

**N/D = NOT DETERMINED (NO DATA) N/E = NONE ESTABLISHED Y = YES**

**N/A = NOT APPLICABLE N/AV = NOT AVAILABLE N = NO**