

Product: Marine Light Penetrating Oil-Liquid**Product #:** 92-881094K 1**SECTION I - MANUFACTURER INFORMATION****Name:** Mercury Marine**Emergency:** 800-424-9300 (ChemTrec)**Address:** W6250 W. Pioneer Rd.**Information:** 920-929-5418

PO Box 1939

Date Prepared: 03-22-01

Fond du Lac WI 54936-1939

Revised:**SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION**

Hazardous Components*	OSHA PEL	ACGIH TLV	Other	% (Opt.)
Distillates, Petroleum, Severely Hydrotreated Heavy Naphthenic (64742-52-5)	5mg/m ³	5mg/m ³		30-50
Kerosene, Petroleum (8008-20-6)	N/E	N/E		50-70
Stoddard Solvent (8052-41-3)	100ppm	100ppm		1-5

*Specific Chemical Identity, Common Name (CAS)

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS**Boiling Point:** ~212°F**Specific Gravity (H₂O=1):** ~1.1**Vapor Pressure (mmhg):** N/D**Melting Point:** N/D**Vapor Density (Air=1):** > 1**Evaporation Rate:** N/D**Solubility in Water:** Insoluble in water.**(Butyl Acetate=1)****Appearance and Odor:** Amber liquid; mild odor**HMIS Rating:** H-2 F-N/D R-N/D P-Section VIII**SECTION IV - FIRE AND EXPLOSION HAZARD DATA****Flash Point (Method Used):** > 351°F (CdOC)**NFPA Rating:** H-2 F-1 R-0 S-N/A**Flammable Limits:** LEL – N/D UEL - N/D**Extinguishing Media:** Water spray, fog, mist, foam, carbon dioxide (CO₂), dry chemicals, sand, dolomite, etc.

Special Fire Fighting Procedures: Use water to keep fire-exposed containers cool and disperse vapors. Water spray may be used to flush spills away from exposures and dilute spills to non-flammable mixtures. Avoid water in straight hose stream; will scatter and spread fire. Keep run-off water out of sewers and water sources. Dike for water control. Use special protective clothing. Regular protection may not be safe. Prevent inhalation of fumes and gases.

Unusual Fire and Explosion Hazards: Volume and pressure increases strongly when heated. Risk of container explosion in fire.

SECTION V - REACTIVITY DATA**Stability:** Unstable () Stable (X)**Conditions to Avoid:** Contact with strong oxidizers. Avoid heat, flames, and other sources of ignition.**Incompatibility (Materials to Avoid):** N/D**Hazardous Decomposition or Byproducts:** Oxides of carbon**Hazardous Polymerization:** May Occur () Will Not Occur (X)**ADDITIONAL INFORMATION**

Mercury Marine Emergency Information Number: 920-929-5000

Manufacturer, Chemtool Inc., Emergency Number: 815-459-1250

SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry: Inhalation (Y) Skin (Y) Eye (Y) Ingestion (Y)

Health Hazards (Acute and Chronic): Harmful by inhalation.

Carcinogenicity: NTP (N) IARC Monographs (N) OSHA Regulated (N)

Signs and Symptoms of Exposure: Inhalation – Oil mist can be harmful. Can irritate airways and lungs. Prolonged inhalation of large concentrations can damage respiratory system. Skin – Concentrate may cause irritation. Eye- Irritating. Ingestion – Can cause stomach ache and vomiting.

Medical Conditions Generally Aggravated by Exposure: N/D

Emergency and First Aid Procedures: Inhalation – Remove victim immediately from source of exposure. Get medical attention if any discomfort continues. For breathing difficulties, oxygen may be necessary. If breathing stops, provide artificial respiration. Skin – Remove affected person from source of contamination. Promptly remove contaminated clothing. Wash contaminated skin with soap or mild detergent and water. Get medical attention if irritation persists after washing. Launder or discard contaminated clothing. Eye – Rinse the eye with water immediately. Continue to rinse for at least 15 minutes. Get medical attention. Ingestion – DO NOT INDUCE VOMITING! Get medical attention immediately.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: Provide good ventilation. Carefully collect spilled material in closed containers and leave for disposal according to local regulations. Rinse area with water. Do not let washing-down water contaminate ponds or waterways. Keep product out of sewers and watercourses by diking or impounding. Advise authorities if product has entered or may enter sewers, watercourses, and extensive land areas. Assure conformity with applicable government applications.

Waste Disposal Method: Dispose of in accordance with local authority requirements. Confirm disposal procedures with environmental engineer and local regulations.

Precautions to be taken in Handling and Storing: Keep away from heat, sparks and open flame. Store separate from acids and oxidizing materials.

Other Precautions: KEEP AWAY FROM CHILDREN!

SECTION VIII - CONTROL MEASURES

Respiratory Protection (Specify Type): No specific recommendation made. Respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

Ventilation: Local Exhaust & Mechanical: No specific ventilation requirements are noted, but forced ventilation may still be required if air contamination exceeds acceptable level.

Protective Gloves: For prolonged or repeated skin contact, use suitable protective gloves. Neoprene, nitrile, polyethylene, or PVC

Eye Protection: Wear chemical safety goggles where eye exposure is reasonably probable.

Other Protective Clothing or Equipment: Wear appropriate clothing to prevent repeated or prolonged skin contact.

Work/Hygiene Practices: Always follow good housekeeping and personal hygiene practices.

N/D = NOT DETERMINED (NO DATA) N/E = NONE ESTABLISHED Y = YES

N/A = NOT APPLICABLE N/AV = NOT AVAILABLE N = NO