

Product: Water Resistant Spray Adhesive-Aerosol**Product #:** 92-881098K 1**SECTION I - MANUFACTURER INFORMATION****Name:** Mercury Marine**Emergency:** 800-424-9300 (ChemTrec)**Address:** W6250 W. Pioneer Rd.**Information:** 920-929-5418

PO Box 1939

Date Prepared: 09-18-00

Fond du Lac WI 54936-1939

Revised:**SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION**

Hazardous Components*	OSHA PEL	ACGIH TLV	Other	% (Opt.)
Acetone (67-64-1)**	750ppm	750ppm		10-30
Propane (74-98-6)	1000ppm	N/E		10-30
Hexane (110-54-3)	50ppm	50ppm		30-50
Butane (106-97-8)	800ppm	800ppm		10-30

*Specific Chemical Identity, Common Name (CAS)

** Ingredient subject to the reporting requirements of SARA 313.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS**Boiling Point:** N/D**Specific Gravity (H₂O=1):** 0.64**Vapor Pressure (mmhg):** N/D**Melting Point:** N/D**Vapor Density (Air=1):** > 1**Evaporation Rate:** < 1**Solubility in Water:** Slightly soluble in water.**(Butyl Acetate=1)****Appearance and Odor:** Aerosol; mild, solvent odor**HMIS Rating:** H-2 F-N/D R-H/D P-Section VIII**SECTION IV - FIRE AND EXPLOSION HAZARD DATA****Flash Point (Method Used):** -155° (Method – N/D)**NFPA Rating:** H-2 F-4 R-0 S-N/A**Flammable Limits:** LEL – 1.2 UEL - 13**Extinguishing Media:** Foam, carbon dioxide (CO₂), dry chemicals, sand, dolomite, etc.**Special Fire Fighting Procedures:** Use water to keep fire-exposed containers cool and disperse vapors. Water spray may be used to flush spills away from exposures and dilute spills to non-flammable mixtures. Avoid water in straight hose stream; will scatter and spread fire. Keep run-off water out of sewers and water sources. Dike for water control. Use special protective clothing. Regular protection may not be safe. Prevent inhalation of fumes and gases. Self-contained breathing equipment and chemical-resistant clothing recommended.**Unusual Fire and Explosion Hazards:** Volume and pressure increases strongly when heated. Risk of container explosion in fire. Explosion risk when heated. Aerosol cans may explode in case of fire.**SECTION V - REACTIVITY DATA****Stability:** Unstable () Stable (X)**Conditions to Avoid:** Avoid contact with acids and oxidizing substances. Avoid heat, flames, and other sources of ignition.**Incompatibility (Materials to Avoid):** N/D**Hazardous Decomposition or Byproducts:** Oxides of carbon and hydrocarbons**Hazardous Polymerization:** May Occur () Will Not Occur (X)**ADDITIONAL INFORMATION**

Mercury Marine Emergency Information Number: 920-929-5000

Manufacturer, Chemtool Inc. Emergency Number: 815-459-1250

SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry: Inhalation (Y) Skin (Y) Eye (Y) Ingestion (Y)

Health Hazards (Acute and Chronic): Irritating to eyes, respiratory system, and skin. Acute: Eye and skin irritant. Respiratory system irritant. Chronic: Reports has associated repeated and prolonged occupational exposure to solvents with permanent brain damage and nervous system and other internal organ damage.

Carcinogenicity: NTP (N) IARC Monographs (N) OSHA Regulated (N)

Signs and Symptoms of Exposure: Inhalation – Solvent vapors can be harmful and cause headache, nausea, and intoxication. Prolonged inhalation of larger concentrations can damage respiratory system. Skin – Slightly irritating. Repeated or prolonged contact can result in drying of the skin. Eye – Irritating. Ingestion – Since the quantity in an aerosol can is limited and the product is hard to ingest, the toxicity risk is deemed to be small. Can cause stomach ache and vomiting.

Medical Conditions Generally Aggravated by Exposure: N/D

Emergency and First Aid Procedures: Inhalation – Remove victim immediately from source of exposure. Move the exposed person to fresh air at once. For breathing difficulties oxygen may be necessary. If breathing stops, provide artificial respiration. Get medical attention. Skin – Remove contaminated clothing. Wash affected skin thoroughly with soap and water. Get medical attention if any discomfort continues. Eye – Rinse the eye with water immediately. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues. Ingestion – DO NOT INDUCE VOMITING! Get medical attention immediately.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: Provide good ventilation. Carefully collect spilled material in closed containers and leave for disposal according to local regulations. Rinse area with water. Do not let washing-down water contaminate ponds or waterways. Keep product out of sewers and watercourses by diking or impounding. Advise authorities if product has entered or may enter sewers, watercourses, and extensive land areas. Assure conformity with applicable government regulations.

Waste Disposal Method: Dispose of in accordance with local authority requirements. Confirm disposal procedures with environmental engineer and local regulations.

Precautions to be taken in Handling and Storing: Containers to be kept tightly closed. Store separate from acids and oxidizing materials. Keep away from heat, sparks and open flame. Aerosol cans: Protect against direct sunlight and do not subject to temperatures over 122°F.

Other Precautions: KEEP AWAY FROM CHILDREN!

SECTION VIII - CONTROL MEASURES

Respiratory Protection (Specify Type): No specific recommendation made. Respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

Ventilation: Local Exhaust & Mechanical: No specific ventilation requirements are noted, but forced ventilation may still be required if air contamination exceeds acceptable level.

Protective Gloves: Chemical-resistant gloves required for prolonged or repeated skin contact.

Eye Protection: Wear splash-proof eye goggles to prevent any possibility of eye contact.

Other Protective Clothing or Equipment: Wear appropriate clothing to prevent repeated or prolonged skin contact.

Work/Hygiene Practices: Always follow good housekeeping and personal hygiene practices.

N/D = NOT DETERMINED (NO DATA) N/E = NONE ESTABLISHED Y = YES

N/A = NOT APPLICABLE N/AV = NOT AVAILABLE N = NO