

**Product:** Mercury Racing Blue Metallic Paint (Propellant)**Product #:** 92-822825 1**SECTION I - MANUFACTURER INFORMATION****Name:** Mercury Marine**Emergency:** 800-424-9300 (ChemTrec)**Address:** W6250 W. Pioneer Rd.**Information:** 920-929-5418

PO Box 1939

**Date Prepared:** 04-30-97

Fond du Lac WI 54936-1939

**Revised:** 04-25-03**SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION**

Hazardous Components*	OSHA PEL	ACGIH TLV	Vapor Pressure	% (Opt.)
Propane (74-98-6)	1000ppm	2500ppm	760 mm	22
Butane (106-97-8)	800ppm	800ppm	760 mm	21
Ethylbenzene (100-41-4)**	100ppm	100ppm	7.1 mm	2
Xylene (1330-20-7)**	100ppm	100ppm	5.9 mm	9
Acetone (67-64-1)	1000ppm	500ppm	180 mm	47

\*Specific Chemical Identity, Common Name (CAS)

\*\* This component is listed as a SARA Section 313 Toxic Chemical

**SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS****Boiling Point:** < 0-292°F**Specific Gravity (H<sub>2</sub>O=1):** 0.66**Vapor Pressure (mmhg):** See Section II**Melting Point:** N/A**Vapor Density (Air=1):** > 1**Evaporation Rate:** Greater than Ether**Solubility in Water:** N/A**(Butyl Acetate=1)****Appearance and Odor:** N/D**HMIS Rating:** H-2 F-4 R-0 P-N/D**SECTION IV - FIRE AND EXPLOSION HAZARD DATA****Flash Point (Method Used):** 0°F**NFPA Rating:** N/D**Flammable Limits:** LEL – 1.0 UEL – 12.8**Extinguishing Media:** Carbon dioxide, dry chemical, foam**Special Fire Fighting Procedures:** Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure buildup and possible autoignition or explosion when exposed to extreme heat.**Unusual Fire and Explosion Hazards:** Containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions, overexposure to decomposition products may cause a health hazard.**SECTION V - REACTIVITY DATA****Stability:** Unstable ( ) Stable (X)**Conditions to Avoid:** None known.**Incompatibility (Materials to Avoid):** None known.**Hazardous Decomposition or Byproducts (Thermal):** Carbon dioxide, carbon monoxide**Hazardous Polymerization:** May Occur ( ) Will Not Occur (X)**ADDITIONAL INFORMATION**

Mercury Marine Emergency Information Number: 920-929-5000

Manufacturer, Sherwin Williams Co., Emergency Number: 216-566-2917

**SECTION VI - HEALTH HAZARD DATA**

**Route(s) of Entry:** Inhalation ( ) Skin ( ) Eye ( ) Ingestion ( )

**Health Hazards (Acute and Chronic):** Irritation of eyes, skin, and upper respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

**Carcinogenicity: Ethylbenzene** NTP (N) IARC Monographs (2B) OSHA Regulated (N)

**Carcinogenicity: Remaining Components:** NTP (N) IARC Monographs (N) OSHA Regulated (N)

**Signs and Symptoms of Exposure:** Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists. Redness and itching or burning sensation may indicate eye or excessive skin exposure.

**Medical Conditions Generally Aggravated by Exposure:** None generally recognized.

**Emergency and First Aid Procedures:** Inhalation – Remove victim from exposure. Restore breathing. Keep warm and quiet. Skin – Remove contaminated clothing. Wash affected skin area thoroughly with soap and water. Launder contaminated clothing before reuse. Eye – Flush eyes with large amounts of water for 15 minutes. Get medical attention. Ingestion – Do not induce vomiting. Get medical attention immediately.

**SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE**

**Steps to be Taken in Case Material is Released or Spilled:** Remove all sources of ignition. Ventilate the area. Remove with inert absorbent.

**Waste Disposal Method:** Waste from this product may be hazardous as defined under the RCRA 40 CFR 261. Waste must be treated for ignitability to determine the applicable EPA hazardous waste numbers. Do not incinerate. Depressurize container. Dispose of in accordance with federal, state/provincial, and local regulations.

**Precautions to be taken in Handling and Storing:** Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively. Keep area ventilated. Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120°F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally.

**Other Precautions:** KEEP AWAY FROM CHILDREN!

**SECTION VIII - CONTROL MEASURES**

**Respiratory Protection (Specify Type):** If personal exposure cannot be controlled below applicable exposure limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section II.

**Ventilation: Local Exhaust** (Preferable) **Mechanical** (N/D) – General exhaust acceptable if exposure to materials in Section II is maintained below applicable exposure limits.

**Protective Gloves:** None for normal application. For long or repeated contact, wear chemical-resistant gloves.

**Eye Protection:** Safety glasses with unperforated sideshields.

**Other Protective Clothing or Equipment:** N/D

**Work/Hygiene Practices:** Always follow good housekeeping and personal hygiene practices.

N/D = NOT DETERMINED (NO DATA) N/E = NONE ESTABLISHED Y = YES

N/A = NOT APPLICABLE N/AV = NOT AVAILABLE N = NO