

**Product:** Quicksilver-Force-Bayliner Blue Brush Touch-Up - Bottle

**Product #:** F5H218 (As of 03-31-93, this product is no longer available)

### SECTION I - MANUFACTURER INFORMATION

**Name:** Mercury Marine  
**Address:** W6250 W. Pioneer Rd.  
 PO Box 1939  
 Fond du Lac WI 54936-1939

**Emergency:** 800-424-9300 (ChemTrec)  
**Information:** 920-929-5418  
**Date Prepared:** 05-18-89  
**Revised:** 06-27-89

### SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components*	OSHA PEL	ACGIH TLV	V.P.	LEL	% (Opt.)
Mineral Spirits (64742-88-7)	500ppm	100ppm	2.0	1.0	2.14
PM Acetate (108-65-6)	N/A	N/A	3.7	1.3	2.14
Xylene (1330-20-7)	100ppm	100ppm	5.1	1.0	15.47
Toluene (108-88-3)	200ppm	100ppm	22.0	1.2	28.67
Methyl Isobutyl Ketone (108-10-1)	100ppm	100ppm	15.0	1.2	12.03
Acetone (67-64-1)	1000ppm	750ppm	186.0	2.6	5.00

\* Specific Chemical Identity, Common Name (CAS)

### SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

**Boiling Point:** 175 to 340°F  
**Vapor Pressure (mmhg):** See Section II  
**Vapor Density (Air=1):** > 1  
**Solubility in Water:** Negligible  
**Appearance and Odor:** Opaque liquid, solvent odor

**Specific Gravity (H<sub>2</sub>O=1):** N/D  
**Melting Point:** N/D  
**Evaporation Rate:** < 1  
**(Butyl Acetate=1)**

### SECTION IV - FIRE AND EXPLOSION HAZARD DATA

**Flash Point (Method Used):** 63°F  
**Flammable Limits:** LEL - See Section II UEL - N/D  
**Extinguishing Media:** Use (NFPA) Class B extinguisher, Carbon Dioxide, or foam  
**Special Fire Fighting Procedures:** Fight fire from safe distance. Wear full protective equipment including SCBA.  
**Unusual Fire and Explosion Hazards:** Pressure buildup due to heat exposure may cause containers to explode. Water may be used to cool ruptured containers.

### SECTION V - REACTIVITY DATA

**Stability:** Unstable ( ) Stable (X)  
**Conditions to Avoid:** High temperatures and open flames  
**Incompatibility (Materials to Avoid):** Unknown  
**Hazardous Decomposition or Byproducts:** Carbon Monoxide or Carbon Dioxide  
**Hazardous Polymerization:** May Occur ( ) Will Not Occur (X)

### ADDITIONAL INFORMATION

Mercury Marine Emergency Information Number: 920-929-5000  
 Manufacturer, Custom-Pak Products Inc., Emergency Number: 800-688-4005

**SECTION VI - HEALTH HAZARD DATA**

**Route(s) of Entry:** Inhalation (Y) Skin (Y) Ingestion (Y)

**Health Hazards (Acute and Chronic):** **Acute:** Anesthetic effect. Irritation of the respiratory tract or acute nervous system depression characterized by headache, dizziness, staggering gait, confusion, unconsciousness, or coma. **Chronic:** Reports have associated repeated and prolonged occupational overexposure to solvents with liver, kidney, brain, and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**Carcinogenicity:** NTP (N) IARC Monographs (N) OSHA Regulated (N)

**Signs and Symptoms of Exposure:** Eye - May cause redness, irritation, tearing, and blurred vision. Skin - May dry skin causing cracks and irritation. Ingestion - May be harmful or fatal if swallowed.

**Medical Conditions Generally Aggravated by Exposure:** Asthma and other respiratory ailments. Chemical sensitization.

**Emergency and First Aid Procedures:** Inhalation - Remove from exposure. Administer oxygen if necessary. Call a physician. Eye - Immediately flush with water for at least 15 minutes. Get medical attention. Skin - Remove contaminated clothing and shoes. Wash contact area with soap and water. Wash clothing and shoes before reuse. Ingestion - Drink 1 or 2 glasses of water to dilute. DO NOT INDUCE VOMITING. Consult a physician or Poison Control Center immediately.

**SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE**

**Steps to be Taken in Case Material is Released or Spilled:** Eliminate all ignition sources. Provide ventilation. Collect spills with absorbent materials and non-sparking tools. See Section VIII for protective equipment.

**Waste Disposal Method:** Dispose of in accordance with Federal, State, and Local regulations. Do not incinerate containers.

**Precautions to be taken in Handling and Storing:** Do not store in areas above 100°F or near fire or open flame. When storing large quantities, storage conditions should comply with OSHA 1910.106. Prevent prolonged or repeated breathing of vapor or spray mist. Do not take internally. Use with adequate ventilation.

**Other Precautions:** KEEP AWAY FROM CHILDREN!

**SECTION VIII - CONTROL MEASURES**

**Respiratory Protection (Specify Type):** In open areas with unrestricted ventilation, a NIOSH/MSHA approved respirator may be used if prolonged and repeated exposure is likely. In areas with restricted ventilation, the use of an approved chemical/mechanical filter designed to remove both particles and vapors is recommended.

**Ventilation: Local Exhaust & Mechanical** - Supply sufficient ventilation to keep air contaminant concentration below current PEL or TLV.

**Protective Gloves:** Use if contact is likely

**Eye Protection:** Safety glasses

**Other Protective Clothing or Equipment:** N/A

**Work/Hygiene Practices:** Always follow good housekeeping and personal hygiene practices.

N/D = NOT DETERMINED (NO DATA) N/E = NONE ESTABLISHED Y = YES

N/A = NOT APPLICABLE N/AV = NOT AVAILABLE N = NO

**Pursuant to Proposition 65:** Certain raw materials used in making this product may contain small amounts of materials as impurities which are regulated by Proposition 65 which applies to a list of chemical names by the Governor of California as carcinogens or reproductive toxins. Warning requirements for specific chemicals take effect one year after they are added to the Governor's List. Other chemicals already added to the Governor's List will be regulated later under Proposition 65.