


Part 1: Leather/Vinyl/Hard Plastic Paint (Page 1-6)

Part 2: Aerosol Touch-Up (Page 7-14)



Revision: 03/16/2004

Printed: 03/17/2004

Date Created: 03/16/2004

1. Product and Company Identification

Product Code: Quicksilver Stencil Kit Black MSDS 058-1002
Part Number: 92-823287
Product Name: Leather/Vinyl/Hard Plastic Paint - Various Colors
Company Name: Mercury Marine
 P.O. Box 1939
 Fond du Lac, WI, 54935
Emergency Contact 1 Information Contact: U.S. Only (ChemTrec) (800) 424-9300
 (920) 929-5000

2. Composition/Information on Ingredients

Hazardous Components (Chemical Name)	CAS #	Percentage	OSHA TWA	ACGIH TWA	Other Limits
1. Toluene	108-88-3	5.0 -8.0 %	200 ppm	50 ppm	150ppm
2. Proprietary	NA	0.5 -5.0 %	No data.	No data.	No data.
3. Methyl ethyl ketone	78-93-3	7.0 -12.0 %	200 ppm	200 ppm	300ppm
4. Acetone	67-64-1	20.0 -35.0 %	1000 ppm	500 ppm	750ppm
5. Proprietary ingredients	NA	5.0 -10.0 %	No data.	No data.	No data.
6. Butyl benzyl phthalate	85-68-7	0.1 -0.9 %	No data.	No data.	No data.
7. Acetic acid, Ethyl ester	141-78-6	5.0 -10.0 %	400 ppm	400 ppm	No data.
8. Methyl isobutyl ketone	108-10-1	5.0 -10.0 %	100 ppm	50 ppm	3mg/m3
9. Dimethyl ether	115-10-6	40.0 -50.0 %	No data.	No data.	No data.

Hazardous Components (Chemical Name)	RTECS #	OSHA STEL	OSHA CEIL	ACGIH STEL	ACGIH CEIL
1. Toluene	XS5250000	500 ppmv(10min)	300 ppm	No data.	No data.
2. Proprietary	NA	No data.	No data.	No data.	No data.
3. Methyl ethyl ketone	EL6475000	No data.	No data.	300 ppm	No data.
4. Acetone	AL3150000	No data.	No data.	750 ppm	No data.
5. Proprietary ingredients	NA	No data.	No data.	No data.	No data.
6. Butyl benzyl phthalate	TH9990000	No data.	No data.	No data.	No data.
7. Acetic acid, Ethyl ester	AH5425000	No data.	No data.	No data.	No data.
8. Methyl isobutyl ketone	SA9275000	No data.	No data.	75 ppm	No data.
9. Dimethyl ether	PM4780000	No data.	No data.	No data.	No data.

3. Hazards Identification

Emergency Overview

WARNING: FLAMMABLE LIQUID AND VAPOR. CONTENTS UNDER PRESSURE. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL.

Route(s) of Entry: Inhalation? Yes Skin? Yes Eyes? Yes Ingestion? Yes

Potential Health Effects (Acute and Chronic)

ACUTE: Irritation of the eyes, skin, and respiratory system. May cause nervous system depression. Extreme overexposure may result in heart irregularities, unconsciousness and possibly death. Direct exposure to liquid propellant may result in frostbite.

CHRONIC: Some formulations of paint may contain carbon black. Carbon black is classified by IARC as possibly carcinogenic to humans (group 2B) based on experimental animal data. However, there is insufficient evidence in humans for its carcinogenicity.

Methyl Ethyl Ketone may increase the nervous system effects of other solvents. Prolonged overexposure of solvent ingredients in Section

MATERIAL SAFETY DATA SHEET

Leather/Vinyl/Hard Plastic Paint

Page: 2

Printed: 03/17/2004

Revision: 03/16/2004

2 may cause adverse effects to the liver, urinary, blood forming, cardiovascular, and reproductive systems. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Signs and Symptoms Of Exposure

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists. Redness and itching or burnig sensation may indicate eye or excessive skin exposure.

Medical Conditions Generally Aggravated By Exposure

None generally recognized.

OSHA Hazard Classes:

HEALTH HAZARDS : Toxic, Irritant

PHYSICAL HAZARDS : Compressed Gas, Flammable Liquid/Sol

TARGET ORGANS & EFFECTS: Heart, Eyes, Skin, Central Nervous System, Respiratory System

4. First Aid Measures

Emergency and First Aid Procedures

If INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet.

If on SKIN: Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before reuse.

If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.

If SWALLOWED: Never give anything by mouth to an unconscious person. DO NOT INDUCE VOMITING. Give conscious patient several glasses of water. Seek medical attention.

Note to Physician

Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with special caution only in situations of emergency life support.

5. Fire Fighting Measures

Flash Point < 20.00 F (-6.7 C) Method: Estimate

Explosive Limits: LEL: No data. UEL: No data.

Autoignition Point No data.

Fire Fighting Instructions

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Flammable Properties and Hazards

Extremely flammable vapors. Vapors are heavier than air and may travel to source of ignition and flash back. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks, and open flame. Closed containers may explode when exposed to extreme heat. During emergency conditions, overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

Extinguishing Media

Carbon dioxide, Dry chemical, Foam

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled

Remove all sources of ignition. Ventilate and remove with inert absorbent.

Leather/Vinyl/Hard Plastic Paint

7. Handling and Storage

Precautions To Be Taken in Handling

Keep away from heat, sparks, and open flame. During use and until all vapors are gone: Keep area ventilated. Do not smoke. Extinguish all flames, pilot lights, and heaters. Turn off stoves, electrical tools and appliances, and any other sources of ignition.

This coating may contain materials classified as nuisance particles listed as "dust" in Section 2 which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10mg/m3 (total dust), 3mg/m3 (respirable fraction), OSHA PEL 15 mg/m3 (total dust), 5 mg/m3 (respirable fraction).

Contents under pressure. Do not puncture, incinerate, or expose to temperatures above 120 F. Protect from heat and sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children.

Precautions To Be Taken in Storing

Do not store above 120 F, or near heat, sparks, open flame, or any other ignition source. Do not store in direct sunlight.

Other Precautions

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

8. Exposure Controls/Personal Protection

Respiratory Equipment (Specify Type)

If personal exposure can not be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2. When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

Eye Protection

Wear safety spectacles with unperforated sideshields.

Protective Gloves

For long or repeated contact, wear chemical resistant gloves.

Engineering Controls (Ventilation etc.)

General exhaust is normally acceptable provided it is adequate to ensure that the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

This product may contain materials classified as nuisance particles or dust which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section II, the applicable limits for nuisance dusts are ACGIH TLV 10mg/m3 (total dust), 3mg/m3 (respirable fraction), OSHA PEL 15mg/m3 (total dust), 5mg/m3 (respirable fraction).

Work/Hygienic/Maintenance Practices

Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

9. Physical and Chemical Properties

Physical States:	[X] Gas	[X] Liquid	[] Solid
Melting Point	No data.		
Boiling Point	No data.		
Specific Gravity	0.8	- 1.0	
Density	No data.		
Vapor Pressure	No data.		
Vapor Density	> Air		
Evaporation Rate	> 1		
Solubility in Water:	No data.		

Leather/Vinyl/Hard Plastic Paint

Percent Volatile:	> 80.000 % by weight.
VOC / Volume:	0.0000
HAP / Volume:	0.0000
Saturated Vapor Concentration:	No data.
Viscosity:	No data.
pH:	No data.

Appearance and Odor
Colored red liquid, paint odor.

10. Stability and Reactivity

Stability: Unstable [] Stable [X]

Conditions To Avoid - Instability

Explosive peroxides may be formed at low rate (compared to diethyl and diisopropyl ethers) upon long exposure to air. Do not concentrate by distillation or evaporation.

Incompatibility - Materials To Avoid

Oxygen, oxidizing chemicals, carbon monoxide, acetic acids, organic acid anhydrides and powdered metals.

Hazardous Decomposition Or Byproducts

By fire: Carbon Dioxide, Carbon Monoxide. If heated with peroxides present, violent decomposition can occur.

Hazardous Polymerization: Will occur [] Will not occur [X]

Conditions To Avoid - Hazardous Polymerization

No data available.

11. Toxicological Information

Toxicological Information

Dimethyl Ether:

Inhalation 4 hours LC50: 164,000 ppm in rats

Toxic effects in animals from inhalation exposure include anaesthetic effects and decreased blood pressure. Cardiac sensitization occurred in dogs exposed to concentrations of 20% or greater. Repeated exposure caused changes in white blood cell counts, anaesthesia, and reduced weight gain. Long-term exposure of rats to 20,000 ppm caused liver weight reduction and alterations of liver enzymes levels. In another study, observations include decreased red blood cell counts, spleen changes, and decreased survival of males at 10,000 and 25,000 ppm; red blood cell destruction (hemolysis) occurred at 25,000 ppm.

Carcinogenicity/Other Information

Carbon Black is classified by IARC as possibly carcinogenic to humans (group 2B) based on experimental animal data. However, there is insufficient evidence in humans for its carcinogenicity.

Carcinogenicity: NTP? No IARC Monographs? No OSHA Regulated? No

12. Ecological Information

Ecological Information

No data available.

13. Disposal Considerations

Waste Disposal Method

Waste of this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers. Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

MATERIAL SAFETY DATA SHEET

Leather/Vinyl/Hard Plastic Paint

RCRA Waste ID Code: D001

14. Transport Information

LAND TRANSPORT (US DOT)

DOT Proper Shipping Name

Aerosols, flammable, 2.1, UN1950, Ltd. Qty.

DOT Hazard Class: 2.1

DOT Hazard Label: Flammable Gas

UN/NA Number: UN1950

Additional Transport Information

May be reclassified as a Consumer Commodity ORM-D per 49CRF.

15. Regulatory Information

US EPA SARA Title III

Hazardous Components (Chemical Name)	CAS #	Sec.302 (EHS)	Sec.304 RQ	Sec.313 (TRI)	Sec.110
1. Toluene	108-88-3	No	Yes 1000 LB	Yes	Yes
2. Proprietary	NA	No	No	No	No
3. Methyl ethyl ketone	78-93-3	No	Yes 5000 LB	Yes	Yes
4. Acetone	67-64-1	No	Yes 5000 LB	No	Yes
5. Proprietary ingredients	NA	No	No	No	No
6. Butyl benzyl phthalate	85-68-7	No	Yes 100 LB	No	Yes
7. Acetic acid, Ethyl ester	141-78-6	No	Yes 5000 LB	No	No
8. Methyl isobutyl ketone	108-10-1	No	Yes 5000 LB	Yes	Yes
9. Dimethyl ether	115-10-6	No	No	No	No

US EPA CAA, CWA, TSCA

Hazardous Components (Chemical Name)	CAS #	EPA CAA HAP,ODC	EPA CWA NPDES	EPA TSCA	CA PROP 65
1. Toluene	108-88-3	HAP	Yes	8A CAIR ,8A PAIR	Yes
2. Proprietary	NA	No	No	No	No
3. Methyl ethyl ketone	78-93-3	HAP	No	8A PAIR	No
4. Acetone	67-64-1	No	No	No	No
5. Proprietary ingredients	NA	No	No	No	No
6. Butyl benzyl phthalate	85-68-7	No	Yes	8A PAIR	No
7. Acetic acid, Ethyl ester	141-78-6	No	No	8A PAIR	No
8. Methyl isobutyl ketone	108-10-1	HAP	No	8A PAIR	No
9. Dimethyl ether	115-10-6	No	No	No	No

SARA (Superfund Amendments and Reauthorization Act of 1986)

- Sec.302:** EPA SARA Title III Section 302 Extremely Hazardous Chemical with TPQ. * indicates 10000 LB TPQ if not volatile.
- Sec.304:** EPA SARA Title III Section 304: CERCLA Reportable + Sec.302 with Reportable Quantity. ** indicates statutory RQ.
- Sec.313:** EPA SARA Title III Section 313 Toxic Release Inventory. Note: -Cat indicates a member of a chemical category.
- Sec.110:** EPA SARA 110 Superfund Site Priority Contaminant List

Other Important Lists:

- CWA NPDES:** EPA Clean Water Act NPDES Permit Chemical
- CAA HAP:** EPA Clean Air Act Hazardous Air Pollutant
- CAA ODC:** EPA Clean Air Act Ozone Depleting Chemical (1=CFC, 2=HCFC)
- CA PROP 65:** California Proposition 65

TSCA (Toxic Substances Control Act) Lists:

- 5A(2):** Chemical Subject to Significant New Rules (SNURS)
- 6A:** Commercial Chemical Control Rules

Leather/Vinyl/Hard Plastic Paint

8A:	Toxic Substances Subject To Information Rules on Production
8A CAIR:	Comprehensive Assessment Information Rules - (CAIR)
8A PAIR:	Preliminary Assessment Information Rules - (PAIR)
8C:	Records of Allegations of Significant Adverse Reactions
8D:	Health and Safety Data Reporting Rules
8D TERM:	Health and Safety Data Reporting Rule Terminations

Regulatory Information

CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory

EPA Hazard Categories:

This material meets the EPA 'Hazard Categories' defined for SARA Title III Sections 311/312 as indicated:

- Yes No Acute (immediate) Health Hazard
- Yes No Chronic (delayed) Health Hazard
- Yes No Fire Hazard
- Yes No Reactive Hazard
- Yes No Sudden Release of Pressure Hazard

16. Other Information

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Vendor assumes no responsibility for injury to vendee or third person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes all risk in use of the material.

Additional Information About This Product

Mfr: Custom Aerosol Packaging 543 Staunton St. P.O. Box 7411 Piqua, OH 45356

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, expressed or implied, and assume no liability in connection with any use of this information.

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

CHEMICAL PRODUCT IDENTIFICATION:

PRODUCT CODE . . . : Quicksilver Stencil Kit Black MSDS 058-1002
PART NUMBER . . . : 92-823287
PRODUCT CLASS . . . : Aerosol Touch-Up

MSDS PREPARATION DATE: 08/14/2008

Mercury Marine
P.O. Box 1939
Fond du Lac, WI 54935

EMERGENCY TELEPHONE NUMBERS:

24 HOURS A DAY - CALL CHEMTREC: 800-424-9300
Information 8 AM TO 4:30 PM CENTRAL TIME: 262-255-9500

SECTION 2 - COMPOSITION, INFORMATION ON INGREDIENTS

1 ETHYL ACETATE
CAS# 141-78-6
ETHYL ACETATE
PCT BY WT: 16.0000 VAPOR PRESSURE: 76.000 MMHG @ 68F LEL 2.20
EXPOSURE LIMIT:
ACGIH TLV-TWA 400 ppm
ACGIH TLV-STEL NO INFO
OSHA PEL-TWA 400 ppm
COMPANY N.E.

Part 2: Material Safety Data Sheet 058-1002Q

LD50(ORAL) 4935 mg/kg (Rabbit)
LD50(DERMAL) 17962 mg/kg (Rabbit)
LC50 45000 mg/m3 (Mouse)

2 ETHYLBENZENE

CAS# 100-41-4

ETHYLBENZENE

PCT BY WT: .3620 VAPOR PRESSURE: 19.000 MMHG @ 68F LEL 1.20

EXPOSURE LIMIT:

ACGIH TLV-TWA 100 ppm
ACGIH TLV-STEL 125 ppm
OSHA PEL-TWA 100 ppm
OSHA PEL-STEL 125 ppm
OTHER IARC (2B), CALIFORNIA PROP 65 (Cancer 6/11/2004)
LD50(ORAL) 3500 mg/kg (rat)
LD50(DERMAL) 20574 mg/kg (rabbit)
LC50 17623 mg/m3 (rat)

OTHER LIMITS:

PROP 65-Cancer, listed 6/11/04

3 1-METHYL-2-PYRROLIDONE

CAS# 872-50-4

1-METHYL-2-PYRROLIDONE

PCT BY WT: 1.0000 LEL 2.10

EXPOSURE LIMIT:

ACGIH TLV-TWA NO INFO
ACGIH TLV-STEL NO INFO
OTHER CALIFORNIA PROP 65-Developmental (listed 6/15/01)

4 TITANIUM DIOXIDE

CAS# 13463-67-7

TITANIUM DIOXIDE

PCT BY WT: 5.0000

EXPOSURE LIMIT:

ACGIH TLV-TWA 10 mg/m3
ACGIH TLV-STEL NO INFO
OSHA PEL-TWA 10 mg/m3
COMPANY N.E.
LD50(ORAL) > 24000 mg/kg (rat)
LC50 > 6820 mg/m3 (rat)

5 VINYL RESIN

CAS# 9003-22-9

VINYL RESIN

PCT BY WT: 2.0000 LEL 100.00

EXPOSURE LIMIT:

ACGIH TLV-TWA NO INFO
ACGIH TLV-STEL NO INFO

6 XYLENE

CAS# 1330-20-7

XYLENE

PCT BY WT: 2.0000 VAPOR PRESSURE: 6.600 MMHG @ 68F LEL 1.00

EXPOSURE LIMIT:

ACGIH TLV-TWA 100 ppm
ACGIH TLV-STEL 150 ppm
OSHA PEL-TWA 100 ppm
OSHA PEL-STEL 150 ppm
COMPANY N.E.
LD50(ORAL) 4300 mg/kg (rat)
LD50(DERMAL) 1700 mg/kg (rabbit)
LC50 18892 mg/m3 (rat)

7 DIMETHYL ETHER

DIMETHYL ETHER

CAS# 115-10-6

PCT BY WT: 40.0000

LEL 3.40

EXPOSURE LIMIT:

ACGIH TLV-TWA 1000PPM

ACGIH TLV-STEL 1000PPM

8 BUTYL BENZYL PHTHALATE

CAS# 85-68-7

BUTYL BENZYL PHTHALATE

PCT BY WT: 1.0000

LEL .30

EXPOSURE LIMIT:

ACGIH TLV-TWA 5 mg/m3

ACGIH TLV-STEL N.E.

OSHA PEL-TWA 5 mg/m3

OTHER CALIFORNIA PROP 65-Developmental(listed 12/2/05)

9 METHYL ETHYL KETONE

CAS# 78-93-3

METHYL ETHYL KETONE

PCT BY WT: 22.0000 VAPOR PRESSURE: 85.000 MMHG @ 68F LEL 1.80

EXPOSURE LIMIT:

ACGIH TLV-TWA 200 ppm

ACGIH TLV-STEL 300 ppm

OSHA PEL-TWA 200 ppm

COMPANY N.E.

LD50(ORAL) 2737 mg/kg (rat)

LD50(DERMAL) 6480 mg/kg (rat)

LC50 23500 mg/m3 (rat)

This product contains one or more reported carcinogens or suspected carcinogens which are noted NTP, IARC, or OSHA-Z in the other limits recommended column.

This substance is classified as a hazardous air pollutant.

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

- May be fatal if swallowed.
Harmful if inhaled.
Harmful if absorbed through skin.
Causes eye irritation.
Causes skin irritation.
Vapors irritating to eyes and respiratory tract.
Flammable liquid and vapor.
Vapors may cause flash fire or explosion.

EYE:

May cause eye burns.

SKIN:

- May cause skin irritation.
Prolonged contact with the skin can cause chemical burns.
Liquid contact with skin may cause frostbite.
Harmful if absorbed through the skin.
Skin contact may aggravate an existing dermatitis.

INHALATION:

Exposure to high concentrations of vapors may cause dizziness, breathing difficulty, headaches or respiratory irritation.

Part 2: Material Safety Data Sheet 058-1002Q

Extremely high concentrations may cause drowsiness, staggering, confusion, unconsciousness, coma or death.

Excessive inhalation of vapors can cause nasal and respiratory irritation.

Breathing high concentrations of vapors may cause anesthetic effects.

Liquid or vapor may be irritating to skin, eyes, throat or lungs.

Intentional misuse by deliberately concentrating and inhaling the contents of this product can be harmful or fatal.

Respiratory symptoms associated with pre-existing lung disorders may be aggravated by exposure to material(s) in this product.

INGESTION:

Moderately toxic. May cause stomach discomfort, nausea, vomiting, diarrhea, and narcosis.

May cause serious health effects if swallowed.

Aspiration of material into the lungs if swallowed or if vomiting occurs can cause chemical pneumonitis which can be fatal.

May cause nausea, vomiting and diarrhea.

CHRONIC EFFECTS:

Chronic overexposure to a component or components in this material has been found to cause the following effects in laboratory animals:

Kidney damage

Eye damage

Lung damage

Liver damage

Spleen damage

Anemia

Brain damage

Chronic overexposure to a component or components in this product has been suggested as a cause of the following effects in humans:

Liver damage

Cardiac abnormalities

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Repeated breathing or skin contact of methyl ethyl ketone may increase the potency of neurotoxins such as hexane if exposures occur at the same time.

Contains butyl benzyl phthalate which has been shown to cause cancer in at least one study in laboratory animals. Butyl benzyl phthalate is listed by the National Toxicology Program (NTP) as producing significant maternal and developmental toxicity.

Rats exposed to titanium dioxide dust at 250 mg/m³ developed lung cancer, however, such exposure levels are not attainable in the workplace with this material.

There is evidence that repeated long-term exposure to vapor concentrations greater than 50 ppm of n-butyl alcohol may result in some hearing loss.

Product contains toluene which may be harmful to the fetus based on animal studies.

Repeated exposure to toluene has been associated with high frequency hearing loss in laboratory animals. The human consequences of this finding is uncertain.

In April 1996, The International Agency for Research on Cancer (IARC) published Monograph 65 which reclassifies Carbon Black into Group 2B (possibly carcinogenic to humans).

In February 2000 the International Agency for Research on Cancer (IARC) classified ethylbenzene as possibly carcinogenic to humans (Group 2B) on the basis of sufficient evidence for carcinogenicity in experimental animals but inadequate evidence for cancer in humans.

SECTION 4 - FIRST AID MEASURES

EYE CONTACT:

Immediately flush eyes with plenty of water. Get medical attention, if

Sufficient ventilation, in volume and pattern, should be provided to keep air contamination below current applicable OSHA permissible exposure limit or ACGIH's TLV limit.

RESPIRATORY PROTECTION:

If workplace exposure limits are exceeded for any component(see section 2 for hazardous components and exposure limits), a NIOSH/OSHA approved respirator suitable for components listed is recommended.

SKIN PROTECTION:

Chemical resistant plastic or rubber gloves recommended for prolonged or repeated contact.

EYE PROTECTION:

Chemical goggles with side shields or face shield recommended if contact with the eyes is likely.

OTHER PROTECTIVE EQUIPMENT:

Appropriate impervious clothing is recommended if prolonged or repeated contact is likely.

HYGIENIC PRACTICES:

Wash hands before eating or smoking. Smoke in designated areas only.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Vapor Pressure	:	85.00	mm Hg @ 20 C
Vapor Density	:	3.70	
Boiling Range	:	Lower - 77.0	øF
		Higher - 500.0	øF
Specific Gravity	:	.796	
Formula weight per Volume	:	6.6284	LB/GL
VOC (Calculated, LB/GAL)	:	5.812	
VOC (Calculated, GM/L)	:	696.45	
Percent Volatile by weight.	:	87.6874	
Percent Volatile by Volume	:	93.5804	
Evaporation Rate	:	6.000	(n-Butyl Acetate = 1)
Viscosity	:	-N/A	

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID:

Avoid contact with heat, sparks, and open flame.

INCOMPATIBILITIES:

Strong oxidizing agents.
Incompatible with air, and dibenzoyl peroxide

DECOMPOSITION:

Thermal decomposition may produce carbon dioxide, carbon monoxide, and unidentifiable organic materials.

POLYMERIZATION:

No hazardous polymerization will occur under normal conditions.

STABILITY:

The product is stable under normal storage conditions.

SECTION 11 - TOXICOLOGICAL INFORMATION

No specific information is available. Please refer to Section 2 and 3 for available information on exposure limits and hazards identification.

SECTION 12 - ECOLOGICAL INFORMATION

No specific ecological information is available for this product.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:

Place in closed containers. Dispose of product in accordance with local, county, state, and federal regulations.

SECTION 14 - TRANSPORT INFORMATION

Ground shipment of limited or excepted quantities of aerosols or liquid paint in containers of 1 quart or less:

CONSUMER COMMODITY, ORM-D

Ground shipment of liquid paint in containers more than 1 quart:

PAINT, FLAMMABLE LIQUID, UN1263, CLASS 3, GROUP II
(Regulatory sources: DOT 49CFR 172.101)

Air shipment of limited or excepted quantities of aerosols or liquid paint in containers of 1 quart or less:

CONSUMER COMMODITY, ID 8000, CLASS 9 MISCELLANEOUS LABEL

(Regulatory sources: IATA Quantity Exemptions - Table 2.8.4, 2.7.A, 2.7.5, Packaging Instruction: 910)

OR

AEROSOLS, FLAMMABLE, UN1950, CLASS 2.1 LABEL

(Regulatory sources: IATA Quantity Exemptions - Table 2.8.1, 2.8.4, Packaging Instruction: Y203)

SECTION 15 - REGULATORY INFORMATION

SARA 313 INFORMATION:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

ETHYLBENZENE

CAS# 100-41-4 PCT BY WT: .3620

1-METHYL-2-PYRROLIDONE

CAS# 872-50-4 PCT BY WT: 1.0380

XYLENE

CAS# 1330-20-7 PCT BY WT: 2.4140

MIBK - Methyl Isobutyl Ketone

PCT BY WT: 4.7240

*** 4-Methyl-2-pentanone
CAS# 108-10-1 PCT BY WT: 4.7240

FEDERAL REGULATIONS:

TOXIC SUBSTANCES CONTROL ACT: The chemical substances in this product are listed on the TSCA Section 8 inventory.

STATE REGULATIONS:

This product contains chemical(s) which are listed on California's proposition 65 list. If the product is to be sold or used in California a clear and reasonable warning must be provided such as:
warning! This product contains a chemical or chemicals known to the State of California to cause cancer.

warning! This product contains a chemical or chemicals known to the State of California to cause birth defects or other reproductive harm.

NEW JERSEY RIGHT-TO-KNOW

The following non-hazardous ingredients are among the top five components in this product

----- CHEMICAL NAME ----- CAS NUMBER

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at

greater than 3 %

----- CHEMICAL NAME ----- CAS NUMBER

INTERNATIONAL REGULATIONS:

CANADA: The chemical substances in this product are listed on the Canadian Domestic Substances List.

SECTION 16 - OTHER INFORMATION

The information contained on this MSDS is believed to be reliable and accurate. Due to the changing nature of government information, it is impossible to guarantee the accuracy of the information contained herein. Since the conditions of handling and use are beyond our control, we make no guarantee of results and assume no liability for damages incurred by the use of this material. This information should not be regarded as legal advice or regulation. It is the responsibility of the user to comply with all Federal, State, and Local laws and regulations. For questions relating to specific aspects of the requirements and regulations consult the proper regulatory agency.

HMIS RATINGS:

HEALTH: 2* FLAMMABILITY: 4 REACTIVITY: 0 PERSONAL PROTECTION: XP

Supplier; BrynDana International 230 Timberjump Lane

The attached Material Safety Data Sheet relates potential hazards and recommended practices for safe handling of the product that you purchased from Raabe Company.

We urge you and your employees to review the entire MSDS prior to handling, use or disposal of the product.

You are required to keep this MSDS on file for reference by company employees or government regulatory officials.

If you resell or distribute this product, you must furnish a copy of the MSDS to your customer.