

Product: Quicksilver Spray Paint-Mariner Silver**Product #:** 92-97842A12**SECTION I - MANUFACTURER INFORMATION**

Name: Mercury Marine	Emergency: 800-424-9300 (ChemTrec)
Address: W6250 W. Pioneer Rd.	Information: 920-929-5418
PO Box 1939	Date Prepared: 06-22-94
Fond du Lac WI 54936-1939	Revised: 05-12-95

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components*	OSHA PEL	ACGIH TLV	V.P.	% (Opt.)
Propane (74-98-6)	100ppm	N/D	760.00	15
Butane (106-97-8)	800ppm	800ppm	760.00	15
Ethylbenzene (100-41-4)	100ppm	100ppm	7.10	4
Xylene (1330-20-7)	100ppm	100ppm	5.90	20
Acetone (67-64-1)	750ppm	750ppm	180.00	30

* Specific Chemical Identity, Common Name (CAS)

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: < 0 - 292°F	Specific Gravity (H₂O=1): 0.74
Vapor Pressure (mmhg): See Section II	Melting Point: N/A
Vapor Density (Air=1): > 1	Evaporation Rate: > 1
Solubility in Water: N/A	(Butyl Acetate=1)
Appearance and Odor: Gray spray, solvent odor	

SECTION IV - FIRE AND EXPLOSION HAZARD DATA**Flash Point (Method Used):** < 0°F (No method listed)**Flammable Limits:** LEL - 1.0 UEL - 12.8**Extinguishing Media:** Carbon Dioxide, dry chemical, foam**Special Fire Fighting Procedures:** Full protective equipment including SCBA should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible auto-ignition or explosion when exposed to extreme heat.**Unusual Fire and Explosion Hazards:** Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions, overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.**SECTION V - REACTIVITY DATA****Stability:** Unstable () Stable (X)**Conditions to Avoid:** None known**Incompatibility (Materials to Avoid):** None known**Hazardous Decomposition or Byproducts:** By Fire: Carbon Dioxide, Carbon Monoxide**Hazardous Polymerization:** May Occur () Will Not Occur (X)**ADDITIONAL INFORMATION**

Mercury Marine Emergency Information Number: 920-929-5000

Manufacturer, The Specialty Division, Emergency Number: 216-566-2917

SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry: Inhalation (Y) Skin (Y) Eye (Y) Ingestion (Y)

Health Hazards (Acute and Chronic): **Acute:** Irritation of eyes, skin, and respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

Chronic: Prolonged overexposure to solvent ingredients in Section II may cause adverse effects to the liver, urinary and reproductive systems. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Carcinogenicity: NTP (N) IARC Monographs (N) OSHA Regulated (N)

Signs and Symptoms of Exposure: Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists. Redness and itching or burning sensation may indicate eye or excessive skin exposure.

Medical Conditions Generally Aggravated by Exposure: None generally recognized.

Emergency and First Aid Procedures: Inhalation - Remove from exposure. Restore breathing. Keep warm and quiet. Skin - Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use. Eye - Flush eyes with large amounts of water for 15 minutes. Get medical attention. Ingestion - Never give anything by mouth to an unconsciousness person. **DO NOT INDUCE VOMITING!** Give several glasses of water. Seek medical attention.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: Remove all sources of ignition. Ventilate and remove with inert absorbent.

Waste Disposal Method: Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers. Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

Precautions to be taken in Handling and Storing: Store away from heat, electrical equipment, sparks and open flame. Avoid contact with skin and eyes. Wash hands after using.

Other Precautions: KEEP AWAY FROM CHILDREN!

SECTION VIII - CONTROL MEASURES

Respiratory Protection (Specify Type): Wear a properly fitted organic vapor/particulate respirator if exposure cannot be controlled below applicable exposure limits.

Ventilation: Local Exhaust - Preferable **General** - Acceptable if exposure limits can be maintained.

Protective Gloves: Chemical-resistant gloves for long or repeated contact

Eye Protection: Safety glasses with unperforated side shields

Other Protective Clothing or Equipment: None

Work/Hygiene Practices: Always follow good housekeeping and personal hygiene practices.

N/D = NOT DETERMINED (NO DATA) N/E = NONE ESTABLISHED Y = YES
N/A = NOT APPLICABLE N/AV = NOT AVAILABLE N = NO

Pursuant to Proposition 65: Certain raw materials used in making this product may contain small amounts of materials as impurities which are regulated by Proposition 65 which applies to a list of chemicals named by the Governor of California as carcinogens or reproductive toxins. Warning requirements for specific chemicals take effect one year after they are added to the Governor's List. Other chemicals already added to the Governor's List will be regulated under Proposition 65.